

Specialty Tags

Catalog Comparison Guide



🌐 Global



🌐 Global



🌐 Global

🌐 Global 📄 High Memory

Product Name	Adept 400	Adept 400	Adept 500	Adept 850	Adept 360°	
Typical Applications	Piping Valves Processing Equipment	Piping Valves Processing Equipment	Gas Cylinders Beverage Kegs	Manufacturing & Supply Chain Automotive Outdoor & Industrial Operations	Very heavy industry applications. Identification of lifting equipment for maintenance and inventory management	
RF Specifications	Frequency Range (MHz)	860-930 (GS)	860-930 (GS)	902-928 (US only)	860-960 (GS)	860-930MHz (GS) 13.56MHz (HF opt.)
	Read Range (m) Fixed reader Handheld reader	Up to 2.25 = 5 layer, Up to 4.0 = 4 layer Up to 1.35 = 5 layer, Up to 2.0 = 4 layer	Up to 4.5 Up to 1.8	Up to 5.0 Up to 5.0	Up to 8.5 Read, Up to 4 Write	Up to 10 (UHF), Up to 0.1 (HF opt) Up to 5.0 (UHF), Up to 0.1 (HF opt)
	Material Compatibility	Optimized for Metal	Optimized for Metal	Optimized for Metal	Optimized for Metal	Metal and non-metallic substrates
	IC Type	Monza 4QT	Alien Higgs 3	Alien Higgs 3	Qstar-5A	Alien H3 (UHF) NXP I-Code (HF opt.)
Physical and Environmental Specifications	Encasement	Stainless Steel with Ceramic Core	Stainless Steel with Ceramic Core	Durable Thermoplastic	ABS	Steel frame
	Size (mm)	45.0 × 30.5 × 15.5 = 5 layer 39 × 30.5 × 11.2 = 4 layer	36.0 × 25.0 × 13.5 = 5 layer 30 × 25 × 8.2 = 4 layer	37.0 × 37.0 × 11.5	65.0 × 45.0 × 8.0	137 × 48.0 × 5.50
	Weight (g)	94.0 = 5 layer, 53.0 = 4 layer	58.0 = 5 Layer, 35.0 = 4 layer	12.5	29.0	126
	Operating Temperature (°C)	-20 to +65	-20 to +65	-20 to +65	-20 to +85	-40 to +85
	Ingress Protection	IP68	IP68	IP68	IP68	IP68
	Shock and Vibration¹	MIL STD 810-G	MIL STD 810-G	MIL STD 810-G	MIL STD 810-G	MIL STD 810-G
	Attachment	Steel strap or welded = 5 layer Epoxy2or welded = 4 layer	Steel strapping or welded = 5 layer Epoxy2or welded = 4 layer	Premium foam (option)	Rivet/screw (not included) Foam or thin film Adhesive (option)	Tether attachment (not included)
Order Codes²	115 – GS For 4 layer, add option code :523	080 – (US only) For 4 layer, add option code :523	045 – GS	114 – GS	032 – GS	

¹ Products tested by third party in line with use case requirements. ² Customer to validate their epoxy. ³ Order Option Codes are listed on the datasheets.

Visit www.omni-id.com to learn more about the complete line of Omni-ID RFID products.

Values for Comparison only, please refer to Product Datasheets for full specifications

Specialty Tags

Catalog Comparison Guide



🌐 Global

Product Name		Fit 400P	Max Rigid	Pipe	Prox NG
Typical Applications		Tool tracking Plastic handles on tools Surface mounting to plastic components of high value assets	Tracking returnable transit items Warehouse storage locations Rail carriage identification	Road Toll Collection Vehicle Access Control Vehicle Permits	Enterprise IT data center asset management
RF Specifications	Frequency Range (MHz)	902–928 (US) 866–868 (EU)	902–928 (US) 866–868 (EU)	902-928 (US) 866-868 (EU)	860-930 (GS)
	Read Range (m) Fixed reader Handheld reader	Up to 3.5 Up to 1.75	Up to 12.0 (US), Up to 10.0 (EU) Up to 6.0 (US), Up to 5.0 (EU)	Up to 12.0 Up to 12.0	Up to 1.8 Up to 0.9
	Material Compatibility	Non-metallic substrates only	Metal and non-metallic substrates	Optimized	Metal & non-metallic substrates
	IC Type	Alien Higgs 3	Alien Higgs 3	Alien Higgs 3	Alien Higgs 3
Physical and Environmental Specifications	Encasement	Ceramic - Painted Black	ABS or Polycarbonate	Polypropylene structure and synthetic label	Synthetic Label
	Size (mm)	17.6 x 7.10 x 4.10	104 x 33.0 x 8.40	79.0 x 74.0 x 20.0	37.5 x 12.5 x 4.5
	Weight (g)	2.10	22.0	44.0	2.2
	Operating Temperature (°C)	-20 to +85	ABS: -40 to +55 Polycarbonate: -40 to +85	-40 to +65	-5 to +55°C
	Ingress Protection	IP68	IP68	IP68	IP54
	Shock and Vibration ¹	MIL STD 810-G	MIL STD 810	MIL STD 810-G	MIL STD 810-G
	Attachment	Film adhesive (included)	Manual (std) Premium Foam adhesive (option)	Strap- not included	Film adhesive & tether hole (std) Premium foam adhesive (option)
Order Codes ²	052 - US, EU	020 – US, EU	030 – US, EU	031 – GS	

¹ Products tested by third party in line with use case requirements. ² Customer to validate their epoxy. ³ Order Option Codes are listed on the datasheets.

Need a Custom Tag?

Our customized and embedded RFID solutions can ensure you know more, about everything, and make critical business decisions faster.

Visit www.omni-id.com/custom-tagging to learn more about the complete line of Omni-ID RFID products.

Visit www.omni-id.com to learn more about the complete line of Omni-ID RFID products.

Values for Comparison only, please refer to Product Datasheets for full specifications