

# Flex Range – Flexible to Fit Many Applications

## Featured Comparison Guide



Product Name		Flex 600	Flex 1200
Typical Applications		Office Equipment Light outdoor use Returnable Transit Items Ideal for portal setups	Office Equipment Light outdoor use Returnable Transit Items Ideal for Portal setups
RF Specifications	Frequency Range (MHz)	902–928 (US) 866–868 (EU)	902–928 (US) 866–868 (EU)
	Read Range (m) Fixed reader Handheld reader	Up to 6.0' on metal, 3.0m off metal Up to 3.0m on metal, 1.5m off metal	Up to 12.0m on metal, 8.0m off metal Up to 6.0m on metal, 4.0m off metal
	Material Compatibility	Metal & non-metallic substrates	Optimized for Metal
	IC Type	Monza R6-P	Monza R6-P
Physical and Environmental Specifications	Coverstock	White synthetic label with transparent over laminate	White synthetic label with transparent over laminate
	Size (mm)	55.8 x 20.0 x 2.50	75.0 x 25.0 x 2.50
	Weight (g)	0.85	1.66
	Operating Temperature (°C) <sup>1</sup>	-40 to +85	-40 to +85
	Ingress Protection	IP68	IP68
	Shock and Vibration	MIL STD 810-G	MIL STD 810-G
	Attachment	Film adhesive (std)	Film adhesive (std)
Order Codes <sup>†</sup>		149 - US, EU	160 - US, EU

<sup>1</sup> Excludes adhesive options, consult adhesive datasheets for recommended temperature ratings. Maximum constant exposure for Fit 220 & 400 = 700 hours and 12 hours for Fit 210. <sup>†</sup> Order option codes are listed on the datasheets.

# Need a Custom Tag?

Our customized and embedded RFID solutions can ensure you know more, about everything, and make critical business decisions faster.

Visit [www.omni-id.com/custom-tagging](http://www.omni-id.com/custom-tagging) to learn more about the complete line of Omni-ID RFID products.

Visit [www.omni-id.com](http://www.omni-id.com) to learn more about the complete line of Omni-ID RFID products.

Values for Comparison only, please refer to Product Datasheets for full specifications